

INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY Signal Mate C091

# C091 M16 - Quicklock



## **Advantages**

Optimal for outdoor use

- No corrosion issues due to the plastic housing
- IP68 rating, sealed against the ingress of water

The Quicklock system enables

- easy handling
- significant time savings during the plugging process
- a secure connection confirmed by click sound of the locking mechanism

#### Areas of Application

- Measuring instruments and equipment
- Factory automation
- Drive systems and components
- Lighting technology

- Entertainment industry
- CCTV / security and camera surveillance
- Signal and low power transmission for various other applications

# Quicklock System



Ι.

To bring the connector together with the receptacle, the nose and recess must point in the same direction 2.

The connector can now be inserted; it locks into the receptacle by itself (confirmation by click sound) 3.

To release the connection the plastic ring must be turned by 30° and the connector can be removed



For more details call +44 (0) 118 916 6928 or email sales@inelcohunter.co.uk



INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY Signal Mate C091

## **Characteristics**

Number of contacts	3	4	5a	5b	6	7a	7b	8	12	14a	14b	19
Rated voltage	150V		100V	32V	10	VC			32V		n	
Current rating	10A / +40C		7A / +40C					3A / +40C				
Pollution degree	3											
Temperature range	-40C to +100C											
IP degree	IP 68 (in mated condition)											
Insertion forces	25N	30N	35	5N	50N	55	5N	60N		50N		60N
Mechanical operation	silver > 500 mating cycles / gold > 1000 mating cycles											
Housing material	thermoplastic											
Dielectric material	thermoplastic											
Sealing material	chlororene, silicone											
Contact plating	silver or gold											
Terminationtechnique	solder / crimp solder										der	
Wire gauge	solder < 0,5mm < 0,35mm									5mm		
Flammability	UL 94 VO											
Locking system	Quicklock System											

# Check out the Signal Mate C091 product range!



#### For more details call +44 (0) 118 916 6928 or email sales@inelcohunter.co.uk