



Unleash the potential of your business, with our range of 3.5", 4.3", 5", 7" and 10.1" STM32 displays



Features:

- Arm Cortex-M7 MCU, with 480MHz core
- 16MB SDRAM and 32MB QSPI Flash
- 8GB EMMC (Optional)
- On-board USB, I2C, UART, CAN, SPI
- microSD card interface
- Supports RTC
- Reconfigurable GPIO for flexible design
- 450cd/m² or 1,000 cd/m² brightness
- 1280x800px resolution
- On-board 10/100 Base-T Ethernet interface with PHY IC built in

Benefits:

- Full viewing angle display (80/80/80/80)
- TouchGFX application templates with free BSP
- PCAP touch screen
- Easy Integration for panel or flush mounting
- Backlight control via PWM
- Single power source
- Pre-assembled Touch screen display and STM32 Interface board

Applications

The potential uses are enormous, encompassing a wide range of applications, including HVAC coolers, industrial automation, medical devices, home technology, IoT products, communication systems and more.



Industrial HVAC/HMI Controller



Medical Devices and Applications



Fire & Security Panels



Smart Home / BMS Systems

Smart Product, Smart Choice

Size (inches)	Part No.	Brightness	Resolution	Power Supply
3.5	JXMA320240T028-ZHC	850 cd/m ²	320 x 240 114 PPI	5V
4.3	JXMA480272T016-ZHC	850 cd/m ²	480 x 272 138PPI	5V
5	JXMA800480T030-ZHC	850 cd/m ²	800 x 480 186 PPI	5V
7	JXMA102600T013-ZHC05	1,000 cd/m ²	1024 x 0600 169 PPI	12V
10.1	JXMA128800T004-ZFC07	450 cd/m ²	1280 x 0800 149 PPI	12V
10.1	JXMA128800T004-ZZC11	1,000 cd/m ²	1280 x 0800 149 PPI	12V

Tel: +44 (0) 1189 166 928

Email: sales@inelcohunter.co.uk

Visit: www.inelcohunter.co.uk