

# POWER RELAY

## 1 POLE - 16A, 85°C TYPE (ATEX COMPLIANT)

### FTR-K1 Series

RoHS Compliant

#### ■ FEATURES



- Compliant to IEC/EN60079-0, IEC/EN60079-1 EU ATEX Directive (type of protection "dc") for use in hazardous location
- Low profile (height: 15.7mm)
- High insulation
- Insulation distance (between coil and contacts): 10mm minimum, dielectric strength: 5,000V, surge strength: 10,000V
- Class F coil wire
- Low coil power (400mW)
- Cadmium free contacts
- Safety standards: cULus, VDE, CQC approved
- Flux proof, RTII
- Plastic material: UL94V-0 flammability
- RoHS compliant



#### ■ APPLICATIONS

Heater control, home appliances, lighting equipment etc. used in hazardous location

#### ■ PART NUMBERS

[Example] FTR-K1   A   K   012   I - B  
 (a)   (b)   (c)   (d)   (e)   (f)

(a)	Relay type	FTR-K1 series
(b)	Contact configuration	A : 1a (1 Form A, SPST-NO) C : 1c (1 Form C, SPDT)
(c)	Coil type	K : Standard type (400mW)
(d)	Coil rated voltage	012 : 12, 24VDC Please refer to coil rating table
(e)	Contact material / TV type	T : AgSnO <sub>2</sub> (1a) W : AgSnO <sub>2</sub> (1c)
(f)	Special type	B : ATEX compliant EB : ATEX compliant, glow wire compliant (material conformity with IEC 60335-1)

Actual marking does not carry the type name: "FTR".

E.g.: Ordering code: FTR-K1AK012T-B Actual marking: K1AK012W-B

## ■ SPECIFICATIONS

Item		Specifications		Remarks/Conditions	
		FTR-K1AK( )T-B FTR-K1AK( )T-EB	FTR-K1CK( )W-B FTR-K1CK( )W-EB		
Contact Data	Configuration	1a (1 Form A)	1c (1 Form C)		
	Construction	Single			
	Material	AgSnO <sub>2</sub>			
	Resistance	Max. 100mΩ		Initial at 1A, 6VDC	
	Contact rating	16A, 250VAC		Resistive	
	Max. carrying current	16A (up to 85°C)			
	Min. switching load *1	100mA, 5VDC			
Coil	Rated power (20°C)	400mW			
	Operate power (20°C)	200mW			
	Operating temperature range	-40°C to +85°C		No frost	
Time	Operate	Max. 15ms		Without bounce	
	Release	Max. 5ms		Without bounce, no diode	
Life	Mechanical	Min. 20 x 10 <sup>6</sup> operations			
	Electrical	Min. 100 x 10 <sup>3</sup> ops.	Min. 50 x 10 <sup>3</sup> ops.		
Insulation	Insulation resistance		Min. 1,000MΩ	At 500VDC	
	Dielectric withstanding strength	Open contacts	1,000VAC (50/60Hz), 1 minute		
		Coil to contacts	5,000VAC (50/60Hz), 1 minute		
	Surge strength	Coil to contacts	10,000V / 1.2 x 50μs standard wave		
	Clearance / creepage		10mm / 10mm		
	EN61810-1,	Voltage	250V		
	EN60335-1,	Pollution degree	3		
	EN60730-1,	Material group	III a		
	EN62368-1	Category	C / 250 (reference voltage) (VDE0110b)		
Others	Vibration resistance	Misoperation≥1μs	10 to 55 to 10Hz single amplitude 0.35mm		Coil ON/OFF, 3 axis, total 6 cycles
		Endurance	10 to 55 to 10Hz single amplitude 0.75mm		Coil OFF, 3 axis, total 6 hours
	Shock resistance	Misoperation≥1μs	Min. 100m/s <sup>2</sup> (11±1ms)		Coil ON/OFF, 3 axis, total 36 operations
		Endurance	Min. 1,000m/s <sup>2</sup> (6±1ms)		Coil OFF, 3 axis, total 18 operations
	Dimensions / Weight		12.7 x 29.0 x 15.7 mm / approx. 13g		
	Sealing		Flux proof, RTII		

Need to consider the heat from PCB when max. current is more than 10A.

\*1: Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

## ■ COIL DATA

Coil Code	Rated Coil Voltage (VDC)	Coil Resistance $\pm 10\%$ ( $\Omega$ )	Must Operate Voltage**1 (VDC)	Must Release Voltage**1 (VDC)	Rated Power (mW)
012	12	360	8.4	1.2	400
024	24	1,440	16.8	2.4	

Note: All values in the table are valid for 20°C and zero contact current unless otherwise specified.

\*: Specified operated values are valid for pulse voltage.

Note: Please use at rated coil voltage. Please refer to characteristic data and set up adequate voltage in case of use at over voltage.

## ■ PART NUMBER LIST

Part Number	Contact Construction	Rated Power	Contact Material	Special Type
FTR-K1AK( )T-B	1a (1 Form A)	Standard (Approx. 400mW)	AgSnO <sub>2</sub>	ATEX compliant
FTR-K1AK( )T-EB				ATEX compliant, glow wire compliant
FTR-K1CK( )W-B	1c (1 Form C)	Standard (Approx. 400mW)	AgSnO <sub>2</sub>	ATEX compliant
FTR-K1CK( )W-EB				ATEX compliant, glow wire compliant

## ■ SAFETY STANDARDS

### ●Certifications

Certified Body/ Type	Certification No./Certified Part Number/ Applicable Standard	Contact Rating	
		1a	1c
cULus	Certification No.E63614 Part number: FTR-K1AK( )T, FTR-K1CK( )W UL Standard: UL60947-1, UL60947-4-1 cUL Standard: CSA-C22.2 No.60947-1 CSA-C22.2 No.60947-4-1	16A, 277VAC (resistive), 85°C	16A, 277VAC (resistive), 85°C
VDE	Certification No.40013848 Part number (special type: B): FTR-K1AK( )T, FTR-K1CK( )W Part number (special type: EB): FTR-K1AK( )T-GW, FTR-K1CK( )W-GW Standard: IEC/EN 61810-1	16A, 250VAC (cosφ=1), 85°C	16A, 250VAC (cosφ=1), 85°C
CQC	Certification No.CQC12002083788 (China) Part number: FTR-K1AK( )T, FTR-K1CK( )W Standard: GB/T 21711.1, IEC 61810-1+GB 4943.1	16A, 250VAC, 85°C	16A, 250VAC, 85°C
	Certification No.CQC14002106809 (Japan) Part number: FTR-K1AK( )T, FTR-K1CK( )W Standard: GB/T 21711.1	16A, 250VAC, 85°C	16A, 250VAC, 85°C

The part numbers on the safety standards' certifications and the ordering part numbers may differ. Coil code is in ( ).

### ●ATEX directive compliance









Certified Body/ Type	Certification No./Certified Part Number/Applicable Standard	Contact Rating	
		1a	1c
UL	UL registration No.UL 21 ATEX 2579U Part number: FTR-K1AK( )T-B, FTR-K1CK( )W-B Standards: IEC/EN 60079-0, IEC/EN 60079-1 Equipment protection level: <del>Ex</del> II 3G Ex dc IIA Gc	16A, 277VAC (resistive), 85°C	16A, 277VAC (resistive), 85°C

Coil code is in ( ).



## CHARACTERISTIC DATA

(Characteristic data is not guaranteed value but measured values of samples from production line.)



## CAUTIONS

- All values mentioned in this datasheet are provided under ideal conditions. Please perform the confirmation test before actual use.
- Reflow soldering is prohibited.
- Do not use relays in the atmosphere with sulfide gas, chloride gas or nitric oxide. Contact resistance may increase.
- Do not use silicon or silicon-containing product or materials near relays. It may cause contact failure.

## GENERAL INFORMATION

### 1. ROHS Compliance

- All relays produced by FCL Components are compliant with RoHS directive 2011/65/EU, including commission delegated directive 2015/863.

### 2. Recommended lead free solder condition

- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.
- Recommended solder for assembly: Sn-3.0Ag-0.5Cu.

#### Flow Solder Condition:

Pre-Heating: Maximum 120°C within 90 sec.  
Soldering: Dip within 5 sec. at 255°C±5°C solder bath  
Relay must be cooled by air immediately after soldering

#### Solder by Soldering Iron:

Soldering Iron: 30-60W  
Temperature: Maximum 340-360°C  
Duration: Maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

## Contact

### Japan

FCL COMPONENTS LIMITED  
Shinagawa Seaside Park Tower  
12-4, Higashi-shinagawa 4-chome,  
Tokyo 140 0002, Japan  
Tel: +81-3-3450-1682  
Email: fcl-contact@cs.fcl-components.com

### North and South America

FCL COMPONENTS AMERICA, INC.  
2055 Gateway Place Suite 480,  
San Jose, CA 95110 USA  
Tel: +1-408-745-4900  
Email: contact@fcl-components.us

### Europe

FCL COMPONENTS EUROPE B.V.  
Diamantlaan 25  
2132 WV Hoofddorp, Netherlands  
Tel: +31-23-556-0910  
Email: info@fcl-components.eu

### Asia Pacific

FCL COMPONENTS ASIA PTE LTD.  
No. 20 Harbour Drive, #07-01B  
Singapore 117612  
Tel: +65-6375-8560  
Email: fcal@fcl-components.com

### China

FCL COMPONENTS (SHANGHAI) CO.,LTD.  
Unit 1105, Central Park - Jing An,  
No.329 Heng Feng Road, Shanghai  
200070, China  
Tel: +86-21-3253 0998  
Email: fcsh@fcl-components.com

### Hong Kong

FCL COMPONENTS HONG KONG CO.,  
LIMITED  
Unit 2313, Seapower Tower, Concordia  
Plaza, No.1 Science Museum Road,  
TST, Kowloon, Hong Kong  
Tel: +852-2881-8495  
Email: fcal@fcl-components.com

Web: [www.fcl-components.com/en/](http://www.fcl-components.com/en/)

---

© 2024 FCL Components Limited. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

FCL Components Products are intended for general use, including without limitation, in personal, household and office environments, in buildings and for ordinary use in the industry. FCL Components Products are not intended to be used in applications where extremely high safety is required ("High Safety Required Applications"), such as, but not limited to, applications in nuclear facilities, in aircraft automatic flight control, in air traffic control, in mass transit system control, in missile launch system, in weapon systems, in medical equipment for life support or any application involving a direct serious risk of physical injury or death.

Please do not use FCL Components Products without securing the sufficient safety and reliability required for the High Safety Required Applications.

In addition, FCL Components shall not be liable against the customer and/or any third party for any claims or damages arising in connection with the use of FCL Components Products in the High Safety Required Applications.

FCL Components warrants that its Products, if properly used and services, will conform to their specification and will be free from defects in material and workmanship for twelve months from delivery.

The implied warranties of merchantability and fitness for a particular purpose and all other warranties, representations and conditions, express or implied by statute, trade usage or otherwise, except as set forth in this warranty, are excluded and shall not apply to the Products delivered.

The contents, data and information in this datasheet are provided by FCL Components Limited as a service only to its user and only for general information purposes. The use of the contents, data and information provided in this datasheet is at the users' own risk.

FCL Components has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

FCL Components Limited and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Nor do FCL Components Limited and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. December 19, 2024.